


Strategic Design and Optimization of Inorganic Sorbents for Cesium, Strontium and Actinides



David Hobbs

Presented at the EMSP High Level Waste Workshop
January 19, 2005



EMSP

Environmental Management Science Program



Co-Principal Investigators

§ May Nyman – Sandia National Laboratories

§ Abraham Clearfield – Texas A&M University

§ Ed Maginn – University of Notre Dame

Outline

- § Goals
- § Benefits
- § Research Strategy
- § Findings
- § Research Plans
- § Acknowledgements

Goals



- § Determine the structural factors of inorganic-based sorbents and ion exchange materials that control selectivity and kinetics for the removal of cesium, strontium and actinides from strongly alkaline waste solutions
- § Apply that understanding to the synthesis of materials with improved cesium, strontium and actinide removal characteristics

Benefits

- § Improved radiochemical separations
- § Increased throughput
- § Reduced solids handling
- § Simplified radiochemical separation flowsheet



Research Strategy

- § Synthesize and measure ion exchange characteristics of titanate, titanate and polyoxometalate materials
- § Determine solid state structures of IX materials
- § Develop molecular models of IX materials
- § Use molecular models to guide synthesis of new IX materials





crystalline silicotitanate
 $\text{Na}_2\text{Ti}_2\text{O}_3(\text{SiO}_4) \cdot 2\text{H}_2\text{O}$ (CST)

monosodium titanate
 $\text{NaTi}_2\text{O}_5\text{H}$ (MST)




sodium nonatitanate
 $\text{Na}_4\text{Ti}_9\text{O}_{20} \cdot x\text{H}_2\text{O}$ (SNT)

Polyoxometalate (IPX)
 $\text{M}_{12}[\text{Ti}_2\text{O}_2][\text{SiNb}_{12}\text{O}_{40}] \cdot 16\text{H}_2\text{O}$
 where M = Na, K




Research Findings

Crystalline silicotitanate (CST)




Substitution of Nb for Ti in framework significantly enhances Cs selectivity

Strontium uptake decreases with increasing ionic strength; influence greater for Nb-CST



Cs Exchanged CST



Less Na in tunnel with Nb-CST


Increased cesium coordination in Nb-CST

Molecular models of CST and Nb-CST agree well with XRD studies

A. Tripathi, D. G. Medvedev, M. Nyman, A. Clearfield ; J. Solid State Chem., 175, 72-83, 2003


Sr Exchanged CST

CST



CN = 10

Nb-CST



CN = 7




Reduced affinity for Sr with Nb-CST due to lower degree of coordination

A. Tripathi, D. Medvedev, A. Clearfield; Journal of Solid State Chemistry, in press

Na-IPX Model

- § 40 possible sites per unit cell
- § Charge neutrality requires 24 Na⁺ per unit cell
- § XRD cannot distinguish Na⁺ and H₂O
- § Molecular modeling indicates 4 sites

Site #	Na Occupancy (%)
1	100
2	98.1
3	53.7
4	7.8



- § Water diffusely located near Sites 2, 3 & 4
- § Good agreement between predicted H₂O content and weight loss measured by TGA
- § Substitution of Nb for Ti reduces Na⁺ population in Site 3


Bonhomme, Larentzos, et al., Inorganic Chem., in press.

Performance of Keggin Chain Materials


§ Keggin chain (IPX) materials remove Sr & actinides

§ Not as effective as MST

§ Na-IPX more effective than K-IPX





Titanosilicates with Pharmacosiderite Structure (TSP)



§ TSP materials do not exchange Cs^+ in HLW media, but do exhibit excellent Sr & actinide removal



§ Sr removal faster with Na-TSP

§ Pu removal faster with K-TSP



SRNL-LWP-2005-00004

Sodium Titanate Materials




Increased Capacity

Sample	168-hour K_d (mL/g)
Baseline MST	50,300
SNL-1	3,490,000
SRTC-1	679,000

§ Excellent affinity for Sr & actinides, but not Cs in HLW solutions

§ Investigate methods to modify morphology

- chemically modified MST exhibits significantly improved Sr/actinide removal performance (EM-21)
- decreased SNT crystallinity improved Sr/actinide removal



Research Plans

- § Identify actinide binding sites for the TSP, Keggin and SNT materials
 - XRD
 - XAFS
- § Complete development of and use molecular models for the design of new derivatives of CST, Keggin, TSP and SNT materials
 - Calculation of water isotherms
 - Calculation of selectivity and distribution coefficients for Cs^+ , Sr^{2+} and UO_2^{2+} versus Na^+ in materials with various framework substitutions
 - Investigate Quench Simulation and Reverse Monte Carlo methods to model amorphous materials

Research Plans

§ Synthesize, characterize and test performance of new derivatives of SNT/MST, CST, TSP, Keggin and trisilicate materials

- Mixed phase SNT/CST
- Metal-substituted TSP (e.g., Ge for Si)
- Cationic layered materials intercalated with anionic polyoxometalates
- Polyoxometalates materials with alternate counterions
- Modified SNT/MST materials

§ Test performance of promising new materials with actual tank waste solutions (SRS)

Acknowledgements

§ SRNL

- M. Duff, M. Blume, L. Thacker, D. DiPrete, C. DiPrete

§ SNL

- S. Thoma, L. Neidel, L. Lybarger, A. Sanchez, F. Bonhomme, T. Alam, M. Rodriguez, B. Cherry, J. Krumhansl, T. Nenoff, A. Sattler

§ Texas A&M

- A. Tripathi, D. Medvedev

§ Notre Dame

- J. Larentzos

§ Georgia Institute of Technology

- J. Bradley, Z. Dai

§ Argonne National Laboratory

- N. Dietz, J. Fortner

§ Pennsylvania State University

- K. Mueller